ABS Upright Cabinets BAKERY REFRIGERATED CABINET VENTILATED INOX

BYX 460

BAKERY

DETAILS

В

NER

Ť

4



Image: Cool HE
Digital ThermostatImage: Cool HE
Liner vertical LEDSuitable for
EuRONORM
shelves or tray
60x400mmImage: Cool HE
Digital ThermostatImage: Cool HE
Liner vertical LEDSuitable for
EuRONORM
shelves or tray
60x400mmImage: Cool HE
Digital ThermostatImage: Cool HE
Liner vertical LEDSuitable for
EuRONORM
shelves or tray
60x400mmImage: Cool HE
Digital ThermostatImage: Cool HE
Liner vertical LEDImage: Cool HE
Liner vertical LEDImage: Cool HE
Digital ThermostatImage: Cool HE
Liner vertical LEDImage: Cool HE
Liner vertical LEDImage: Cool HE
Digital ThermostatImage: Cool HE
Liner vertical LEDImage: Cool HE
Liner vertical LEDImage: Cool HE
Digital ThermostatImage: Cool HE
Liner vertical LEDImage: Cool HE
Liner vertical LEDImage: Cool HE
Digital ThermostatImage: Cool HE
Liner vertical LEDImage: Cool HE
Liner vertical LEDImage: Cool HE
Digital ThermostatImage: Cool HE
Liner vertical LEDImage: Cool HE
Liner vertical LEDImage: Cool HE
Digital ThermostatImage: Cool HE
Liner vertical LEDImage: Cool HE
Liner vertical LEDImage: Cool HE
Digital LE
Digital LE<br


22

R600a

GENERAL FEATURES

EURONORM Refrigerated upright 600x400mm (CLASS B)	•
S/S external cabinet, thermoformed internally	•
Roll-bond evaporator system with fan assisted cooling	•
Automatic compressor cycle defrost	•
Foaming Agent Cyclopentane (65mm per side)	•
Digital Thermostat	•
Inner vertical LED light	•
Removable Gasket	•
Adjustable shelves EURONORM 600x400: 4 Pcs + 1 BOTTOM Shelf	•
Self closing door with double layer tempered glass	•
Lock fitted as standard	•
N.4 S/S Adjustable feet - (Lockable castor as Optional)	•
Stainless steel external handle	•
Energy efficiency class: B	•

PRODUCT DIMENSIONS



TECHNICAL SPECIFICATIONS

Capacity	400 L
Temperature	+2° ~ +8°C
Consumption	0.99 kWh/24h
Rated Power	180 W
Noise level	49 dB(A)
Net Weight	88 Kg
Gross Weight	114 Kg
External Dimensions (WxDxH mm)	740x680x1800
Internal Dimensions (WxDxH mm)	610x475x1460
Packaging dimensions (WxDxH mm)	765x665x1950
Loading quantities 20′/40′/40′HQ	24/51/51

CERTIFICATION





