### **INOX | Saladette**

SALADETTE ▶ GN1/1 VENTILATED ▶ FREEZER ▶ STAINLESS STEEL TOP

## CNX 93V















#### **DETAILS**







Engine room lock fitted as standard



Anti-condensation themal-braker on door frame



Main switch and digital thermostat fitted as standard



Evaporator with anti-corrosion treatment



Removable Gasket



Ventilated unit



handle

#### **GENERAL FEATURES**

| GN1/1 Freezer ventilated saladette (STAINLESS STEEL TOP)           | • |
|--|---|
| Stainless Steel exterior and interior                              | • |
| Ventilated Cooling   | • |
| Evaporator with anti-corrosion treatment                           | • |
| Hot gas defrost system   | • |
| Foaming Agent Cyclopentane (45mm per side)                         | • |
| Digital Thermostat   | • |
| Sliding engine room for a manageble after sales servicing          | • |
| Plastic thermal-braker as chamber body frame                       | • |
| Easy removable condenser filter                                    | • |
| Separated plastic water tray                                       | • |
| Front panel tilted holes for better air circulation                | • |
| Adjustable shelves GN1/1: 3 pcs                                    | • |
| Self closing door (New inner embossed design for a better sealing) | • |
| Removable Gasket   | • |
| Engine room lock fitted as standard                                | • |
| N.2 Adjustable feet in the front + N.4 fix rollers                 | • |
| Energy efficiency class: E   | • |

• [150]

### **TECHNICAL SPECIFICATIONS**

| Capacity                         | 364 L         |
|----------------------------------|---------------|
| Temperature                      | -10° ~ -18°C  |
| Consumption                      | 9.236 kWh/24h |
| Rated Power                      | 276 W         |
| Noise level                      | 48 dB(A)      |
| Net Weight                       | 103 Kg        |
| Gross Weight                     | 127 Kg        |
| External Dimensions (WxDxH mm)   | 1365x700x883  |
| Internal Dimensions (WxDxH mm)   | 1275x586x502  |
| Packaging dimensions (WxDxH mm)  | 1420x750x1050 |
| Loading quantities 20'/40'/40'HQ | 24/48/48      |

#### **CERTIFICATION**





RoHS







# **PRODUCT DIMENSIONS**

