
ABS | Upright Cabinets

REFRIGERATED UPRIGHT ► CLASS A ► WHITE PAINTED

111111111 111111111

.1111111111 1111111111

000000





























DETAILS







Cabinet suitable for N.2 GN1/1 pans



Opening door alarm/High temperature alarm







PRODUCT DIMENSIONS



Blue backlit main



Shelf with small distance between the line and bottom shelf fittes as standard



Rear inner evaporator conveyor

Roll-bond evaporator system with fan assisted cooling Rear inner evaporator conveyor

GENERAL FEATURES

| Inverter compressor | |
|------------------------------------|--|
| Automatic compressor cycle defrost | |

GN2/1 Refrigerated upright (CLIMATE 4 / CLASS A) White external cabinet, thermoformed internally

Foaming Agent Cyclopentane (70mm per side) Digital Thermostat

Opening door alarm/High temperature alarm

Removable Gasket Door: Self closing and reversible door fitted as standard

Lock and main switch fitted as standard Adjustable shelves GN2/1: 4 Pcs + 1 Pcs Bottom

N.2 Adjustable feet + N.2 Rollers at the back

Energy efficiency class: A

TECHNICAL SPECIFICATIONS

| Capacity | 600 L |
|----------------------------------|---------------|
| Temperature | +0°C ~ +8°C |
| Consumption | 0.898 kWh/24h |
| Rated Power | 112.3 W |
| Noise level | 58 dB(A) |
| Net Weight | 92 Kg |
| Gross Weight | 106 Kg |
| External Dimensions (WxDxH mm) | 775x756x1900 |
| Internal Dimensions (WxDxH mm) | 596x572x1628 |
| Packaging dimensions (WxDxH mm) | 835x792x2070 |
| Loading quantities 20'/40'/40'HQ | 20/42/42 |

CERTIFICATION





RoHS









1900