INOX | Counter Cabinets

REFRIGERATED COUNTERS H GN1/1 (700 DEPTH) REMOTE COUNTERS FREEZER

QN 4200SG








GENERAL FEATURES

| GN1/1 Freezer counter (REMOTE ENGINE) | • |
|---|---|
| Stainless Steel exterior and interior | • |
| Ventilated Cooling | • |
| Automatic defrost with electric heater | • |
| Foaming Agent Cyclopentane (70mm per side) | • |
| Digital Thermostat | • |
| Plastic thermal-braker as chamber body frame (Hot pipe system) | • |
| Door: Self closing and reversible door fitted as standard | • |
| Removable Gasket | • |
| Evaporator with anti-corrosion treatment | • |
| Adjustable shelves GN1/1: 8 (N.2 for each door) | • |
| N.6 S/S Adjustable feet - (Lockable castor as Optional) | • |
| Expansion valve/Solenoid Valve set (Optional): for gas R452A or R404a | • |
| Splash back height (100mm) | • |
| Energy efficiency class: - | • |
| | |









DETAILS

FK.





Expansion Evaporator with valve/Solenoid Arti-corrosion Valve set (Optional) treatment


PRODUCT DIMENSIONS

TECHNICAL SPECIFICATIONS

| 41 | 10 L |
|----------------------------------|-------|
| -22° ~ -1 | 8°C |
| N/A kWh/ | 24h |
| 440 | o w |
| ١ | N/A |
| 154 | Kg |
| 192 | Kg |
| ions (WxDxH mm) 2255x700x | 950 |
| ons (WxDxH mm) 1675x560x | 605 |
| sions (WxDxH mm) 2285x730x1 | 075 |
| es 20'/40'/40'HQ 16/32 | /32 |
| es 20'/40'/40'HQ | 16/32 |

((C

RoHS







CERTIFICATION