

INOX | Upright Cabinets

REFRIGERATED CABINETS ► GN2/1-NO FROST ► CHILLER



GENERAL FEATURES

- GN2/1 Refrigerated upright cabinet (CLASS A)
- Stainless Steel exterior and interior
- Plastic thermal-braker anti-condensation as chamber body frame
- Ventilated Cooling
- Inverter compressor
- Evaporator with anti-corrosion treatment
- Automatic defrost with electric heater
- Foaming Agent Cyclopentane (80mm)
- Curved edge for easy cleaning
- Digital Thermostat
- White backlit main switch
- LED light and lock fitted as standard
- Removable Gasket
- Door: Self closing and reversible door fitted as standard
- Foamed door handle
- Adjustable shelves GN2/1: 3 + 1
- N.4 S/S Adjustable feet - (Lockable castor as Optional)
- Energy efficiency class: A

TECHNICAL SPECIFICATIONS

Capacity	546 L
Temperature	-2° ~ +8°C
Consumption	0.723 kWh/24h
Rated Power	73 W
Noise level	50 dB(A)
Net Weight	109.00 Kg
Gross Weight	122.00 Kg
External Dimensions (WxDxH mm)	700x850x2045
Internal Dimensions (WxDxH mm)	534x685x1485
Packaging dimensions (WxDxH mm)	720x870x2110
Loading quantities 20'/40'/40'HQ	21/42/42

CERTIFICATION

CE RoHS

QR 6-5A



ENERGY SAVING



TROPICALIZED UPRIGHT



GAS
R600a



80 mm



ENERGY CLASS
A



CLIMATIC CLASS
5



40°C



LED



Door



Evaporator

DETAILS



The items can be supplied either with adjustable feet or lockable castor



Inverter compressor



Evaporator with anti-corrosion treatment



Inner stainless steel waved guides



Anti-condensation "thermal-braker" on door frame



Lock fitted as standard



Digital control and white backlit main switch




Inner LED light



Cabinet suitable for GN2/1 pans

PRODUCT DIMENSIONS



RIGHTWAY ASIA
We make the world a cooler place