ABS | Upright Cabinets

REFRIGERATED UPRIGHT GN2/1 INOX

<u>QRX 600</u>






GENERAL FEATURES

GN2/1 Refrigerated upright (600 Lt.)	•
Gray coated plate external cabinet and door in stainless steel, thermoformed internally	•
Roll-bond evaporator system with fan assisted cooling	•
Automatic compressor cycle defrost	•
Foaming Agent Cyclopentane (60mm per side)	•
Digital Thermostat	•
Removable Gasket	•
Reversible door	•
Handle along door profile	•
Doors lock fitted as standard	•
Adjustable shelves: 4 Pcs + 1 BOTTOM Shelf	•
N.2 Adjustable feet + N.2 Rollers at the back	•
Energy efficiency class: D	•

PRODUCT DIMENSIONS

600 L +2°C ~ +10°C 1.94 kWh/24h 200 W 57 dB(A) 85 Kg 97 Kg 780x730x1890 660x585x1680 812x757x2030 21/42/42



We make the world a cooler place

TECHNICAL SPECIFICATIONS

Capacity	600 L
Temperature	+2°C ~ +10°C
Consumption	1.94 kWh/24h
Rated Power	200 W
Noise level	57 dB(A)
Net Weight	85 Kg
Gross Weight	97 Kg
External Dimensions (WxDxH mm)	780x730x1890
Internal Dimensions (WxDxH mm)	660x585x1680
Packaging dimensions (WxDxH mm)	812x757x2030
Loading quantities 20′/40′/40′HQ	21/42/42

(€ ℃

RoHS

CERTIFICATION

