## **INOX | Upright Cabinets**

REFRIGERATED CABINETS ► GN2/1-STATIC ► CHILLER



#### **GENERAL FEATURES**

GN2/1 Refrigerated upright cabinet	•
Stainless Steel exterior and interior	•
Static cooling system with fan assisted cooling	•
Condenser with anti-corrosion treatment	•
Bottom side engine room (for comfortable storage in the cabinet)	•
Automatic compressor cycle defrost	•
Digital thermostat with "opening door" and "High temperature" alarm	•
Foaming Agent Cyclopentane (80mm)	•
Removable Gasket	•
LED light and lock fitted as standard	•
Door: Self closing and reversible door fitted as standard	•
Adjustable shelves GN2/1: 5 Pcs	•
Plastic thermal-braker anti-condensation as chamber body frame	•
N.4 Adjustable feet - S/S feet or castor with brake (Option)	•
Energy efficiency class: D	•

### **TECHNICAL SPECIFICATIONS**

Capacity	600 L
Temperature	+2° ~ +8°C
Consumption	2.5 kWh/24h
Rated Power	350 W
Noise level	48 dB(A)
Net Weight	144 Kg
Gross Weight	155 Kg
External Dimensions (WxDxH mm)	740x880x2025
Internal Dimensions (WxDxH mm)	580x710x1430
Packaging dimensions (WxDxH mm)	760x900x2150
Loading quantities 20'/40'/40'HQ	18/39/39

#### **CERTIFICATION**





RoHS

# **QRX 688S**

































**DETAILS** 







Digital thermostat and door lock fitted handle as standard



Foamed door



Easily acces for clean condenser filter



Inner vertical LED light



Multi functional set of guide ("E" form)



Cabinet suitable for



Bottom hole for easily clean and dry the item

#### **PRODUCT DIMENSIONS**









