ABS | Upright Cabinets

REFRIGERATED UPRIGHT ► GLASS DOOR ► INOX



GENERAL FEATURES

400 Lt. Refrigerated upright (GLASS DOOR)	•
Gray external cabinet, thermoformed internally	•
Roll-bond evaporator system with fan assisted cooling	•
Automatic compressor cycle defrost	•
Foaming Agent Cyclopentane (60mm per side)	•
Digital Thermostat	•
Removable Gasket	•
Double tempered glass with Low-e (Low emissivity glasses) and Argon g	jas•
Reversible door	•
Inner horizontal LED light	•
Door with vertical cylindrical handle	•
Doors lock fitted as standard	•
Adjustable shelves: 4 Pcs + 1 BOTTOM Shelf	•
N.2 Adjustable feet + N.2 Rollers at the back	•
Energy efficiency class: A	•

TECHNICAL SPECIFICATIONS

Capacity	400 L
Temperature	M1 (-1°C~+5°C)
Consumption	1.96 kWh/24h
Rated Power	200 W
Noise level	58 dB(A)
Net Weight	77 Kg
Gross Weight	86 Kg
External Dimensions (WxDxH mm)	600x723x1890
Internal Dimensions (WxDxH mm)	480x540x1680
Packaging dimensions (WxDxH mm)	632x737x2030
Loading quantities 20'/40'/40'HQ	27/54/54

CERTIFICATION






RoHS

QRXG 400



DETAILS





PRODUCT DIMENSIONS

