## **INOX | Blast Chillers**

Blast chillers

# **RF 23A**

















#### **DETAILS**





420

640



Anti-condensation "thermal-braker" on door frame





#### **GENERAL FEATURES**

GN2/3 Counter top Blast chiller	•
Stainless Steel exterior and interior	•
Ventilated Cooling with Manual defrost	•
Plastic thermal-braker as chamber body frame (Heated wire)	•
Evaporator with anti-corrosion treatment	•
Foaming Agent Cyclopentane (60mm per side - CFC Free)	•
Digital Thermostat with Buzzer alarm	•
Opening door alarm	•
Error messagge directly in the display	•
Chilling chamber in stainless steel	•
Door microswitch for stop inner fan with open door	•
Needle probe fitted as standard	•
Removable Gasket	•
N.4 Adjustable feet	•
Temperature controlled or temporizated blast chilling cycle	•
Automatic storage mode at the end of blast chilling cycle	•
Energy efficiency class: -	•

1. 31

### **PRODUCT DIMENSIONS**

660

#### Capacity Ch.7Kg/Fr.5Kg Temperature +10°C ~ -38°C Consumption N/A kWh/24h Rated Power 420 W Noise level 55 dB(A) Net Weight 44 Kg Gross Weight 52 Kg External Dimensions (WxDxH mm) 660x640x437 Internal Dimensions (WxDxH mm) 340x365x270 Packaging dimensions (WxDxH mm) 700x680x525

## **CERTIFICATION**





RoHS

96/204/255



Loading quantities 20'/40'/40'HQ

**TECHNICAL SPECIFICATIONS** 



