

# INOX | Blast Chillers

BLAST CHILLER

# RF 58A



## DETAILS



## GENERAL FEATURES

- GN1/1 and EURONORM 600x400mm Upright Blast chiller
- Stainless Steel exterior and interior
- Ventilated Cooling with Manual defrost
- Plastic thermal-braker as chamber body frame (Hot pipe system)
- Evaporator with anti-corrosion treatment
- Foaming Agent Cyclopentane (60mm per side - CFC Free)
- Digital control with Wi-Fi function and Buzzer alarm
- Error message directly in the display
- Chilling chamber in stainless steel
- Door microswitch for stop inner fan with open door
- Prepared for condensation water tray (Not included)
- Reversible door / Needle probe fitted as standard
- Tray configuration: 65mm distance between trays
- N.4 S/S Adjustable feet - (Lockable castor as Optional)
- Temperature controlled or temporized blast cycles (Soft/Hard)
- Automatic storage mode at the end of blast chilling cycle
- ECM Fan (For Low energy consumption/Low noise level)
- Separate button for "ICE CREAM" Cycle
- Separate button for "-40°C" Cycle
- ICE CREAM kit (PANS not included) optional

## TECHNICAL SPECIFICATIONS

Capacity	<b>Ch.15Kg/Fr.10Kg</b>
Temperature	<b>+10°C - -40°C</b>
Consumption	<b>N/A kWh/24h</b>
Rated Power	<b>749 W</b>
Noise level	<b>60 dB(A)</b>
Net Weight	<b>76 Kg</b>
Gross Weight	<b>86 Kg</b>
External Dimensions (WxDxH mm)	<b>760x725x850</b>
Internal Dimensions (WxDxH mm)	<b>640x405x360</b>
Packaging dimensions (WxDxH mm)	<b>800x760x900</b>
Loading quantities 20'/40'/40"HQ	<b>42/86/126</b>

## CERTIFICATION



## PRODUCT DIMENSIONS

