ABS | Upright Cabinets

-50

COOL HEAD

Figure and the the the test 135

FREEZER UPRIGHT ► GLASS DOOR ► INOX

UFXG 2















DETAILS







Foamed door handle



Lock fitted as standard



Evaporator bottom layer



Double vertical LED light along inner door profile



Additional removable shelf

GENERAL FEATURES

| 200 Lt. Freezer upright (GLASS DOOR) | • |
|--------------------------------------------------------------------------------|---|
| S/S external cabinet, thermoformed internally | • |
| Static cooling: fixed evaporator shelves (N.2 Layers, one on the bottom) | • |
| Additional upper removable shelves: 1 Pcs | • |
| Manual Defrost | • |
| Foaming Agent Cyclopentane (70mm per side) | • |
| Triple HEATED tempered glass with Low-e (Low emissivity glasses) and Argon gas | • |
| Digital Thermostat | • |
| Independent back-lit main and lights switches (White color) | • |
| Double vertical LED light along door profile | • |
| Removable Gasket and handle along door profile | • |
| Doors lock fitted as standard | • |
| N.2 Adjustable feet + N.2 Rollers at the back | • |
| Energy efficiency class: - | • |

TECHNICAL SPECIFICATIONS

| Capacity | 200 L |
|----------------------------------|---------------|
| Temperature | -20°C ~ -15°C |
| Consumption | 3.4 kWh/24h |
| Rated Power | 285 W |
| Noise level | 62 dB(A) |
| Net Weight | 49 Kg |
| Gross Weight | 53 Kg |
| External Dimensions (WxDxH mm) | 600x625x853 |
| Internal Dimensions (WxDxH mm) | 458x476x603 |
| Packaging dimensions (WxDxH mm) | 640x660x890 |
| Loading quantities 20'/40'/40'HQ | 54/108/162 |



RoHS

CERTIFICATION





PRODUCT DIMENSIONS



