ABS | Upright Cabinets

URXG 6




GENERAL FEATURES

GN2/1 Refrigerated upright (600 Lt GLASS DOOR)	•
S/S external cabinet, thermoformed internally	•
Roll-bond evaporator system with fan assisted cooling	•
Automatic compressor cycle defrost	•
Foaming Agent Cyclopentane (70mm per side)	•
Double safety tempered glass with Low-e (Low emissivity glasses)	•
Digital Thermostat	•
Independent back-lit main and lights switches (White color)	•
Double vertical LED light along door profile	•
Removable Gasket and handle along door profile	•
Self Closing Door	•
Doors lock fitted as standard	•
Adjustable shelves GN2/1: 4 Pcs + 1 Pcs Bottom	•
N.2 Adjustable feet + N.2 Rollers at the back	•
Energy efficiency class: D	•





PRODUCT DIMENSIONS



RIGHTWAY ASIA We make the world a cooler place

TECHNICAL SPECIFICATIONS

Capacity	600 L
Temperature	+2°C ~ +10°C
Consumption	2.605 kWh/24h
Rated Power	255 W
Noise level	58 dB(A)
Net Weight	84 Kg
Gross Weight	103 Kg
External Dimensions (WxDxH mm)	775x760x1863
Internal Dimensions (WxDxH mm)	633x612x1603
Packaging dimensions (WxDxH mm)	820x760x2000
Loading quantities 20′/40′/40′HQ	21/42/42

(€ ℃

RoHS

CERTIFICATION

